

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product Identifier

Product name: S2S2008-500/TOUCHPOINT500

Chemical name: SANITISER

1.2 Relevant identified uses of the substance or mixture and uses advised against

Intended use: Sanitiser

1.3 Details of the supplier of the safety data sheet

Company name: Safe2Stay Ltd
Meon House, rear of 289 Portswood Road, S'hampton, SO17 2NF, UK

Tel: +44 203 930 1650

Email: info@safe2stay.co.uk

1.4 Emergency telephone number

Emergency tel: +44 1462 413081

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification under CHIP: Eye Irrit. 2: H319; Flam. Aerosol 1: H222; STOT SE 3: H336; -: H229

Most important adverse effects: Extremely flammable aerosol. Pressurised container: may burst if heated. Causes serious eye irritation. May cause drowsiness or dizziness.

2.2 Label Elements

Hazard statements: H222: Extremely flammable aerosol.
H229: Pressurised container: May burst if heated.
H319: Causes serious eye irritation.
H336: May cause drowsiness or dizziness.

Hazard pictograms: GHS02: Flame
GHS07: Exclamation mark



Signal words: Danger

Precautionary statements: P102: Keep out of reach of children.
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211: Do not spray on an open flame or other ignition source.
P251: Do not pierce or burn, even after use.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

2.3 Other Hazards

PBT: This product is not identified as a PBT/vPvB substance

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Mixtures**Hazardous Ingredients:**

Ingredient	EINECS	CAS	PBT/WEL	CLP Classification	Percent
ETHANOL	200-578-6	64-17-5	Substance with a community workplace exposure limit.	Flam. Liq. 2: H225	30-50%
PETROLEUM GASES, LIQUIFIED	270-704-2	68476-85-7	Substance with a community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	30-50%
PROPAN-2-OL	200-661-7	67-63-0	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336	10-30%
METHANOL	200-659-6	67-56-1	-	Flam. Liq. 2: H225; Acute Tox. 3: H331; Acute Tox. 3: H301; STOT SE 1: H370	<1%
DIDECYLDIMETHYL-AMMONIUMCHLORIDE	230-525-2	7173-51-5	-	Skin Corr. 1B: H314; Aquatic Acute 1: H400; Acute Tox. 4: H302	<1%

SECTION 4: FIRST AID MEASURES**4.1 Description of first aid measures**

- Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.
- Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.
- Ingestion:** Wash out mouth with water. Consult a doctor.
- Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor. Move to fresh air.

4.2 Most important symptoms and effects, both acute and delayed

- Skin contact:** There may be irritation and redness at the site of contact.
- Eye contact:** There may be irritation and redness. The eyes may water profusely.
- Ingestion:** There may be soreness and redness of the mouth and throat.
- Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.
- Delayed/immediate effects:** Immediate effects can be expected after short-term exposure.

4.3 Indication of any immediate medical attention and special treatment needed

- Immediate/special treatment** Eye bathing equipment should be available on the premises.

SECTION 5: FIRE FIGHTING MEASURES**5.1 Extinguishing media**

- Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2 Special hazards arising from the substance or mixture

- Exposure hazards:** In combustion emits toxic fumes.

5.3 Advice for fire-fighters

- Advice for fire fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2 Environmental Precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3 Methods and materials for containment and cleaning up

Clean up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4 Reference to other sections

Reference to other sections: Refer to Section 8 of SDS.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3 Specific end use(s)

Specific end use: No data available

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Workplace exposure limits:

Hazardous Ingredient	State	8 hour TWA	15 min. STEL	Respirable dust	
				8 hour TWA	15 min. STEL
ETHANOL	UK	1920 mg/m3	-	-	-
PETROLEUM GASES, LIQUIFIED	UK	1,750mg/m3	2,180mg/m3	-	-
PROPAN-2-OL	UK	999 mg/m3	1250 mg/m3	-	-
METHANOL	UK	266 mg/m3	333 mg/m3	-	-

DNEL / PNEC No data available

8.2 Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves. Chemically resistant gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Environmental Not applicable.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

State: Aerosol
Colour: Colourless
Odour: Odourless
Flash point °C: <23

9.2 Other Information

Other information: No data available.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2 Chemical stability

Chemical stability: Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions. Decomposition may occur on exposure to conditions or materials listed below.

10.4 Conditions to avoid

Conditions to avoid: Heat.

10.5 Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6 Hazardous decomposition products

Hazardous Decomposition products: In combustion emits toxic fumes.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Hazardous ingredients:

ETHANOL

IVN	RAT	LD50	1440	mg/kg
ORL	MUS	LD50	3450	mg/kg
ORL	RAT	LD50	7060	mg/kg

PROPAN-2-OL

IVN	RAT	LD50	1088	mg/kg
ORL	MUS	LD50	3600	mg/kg
ORL	RAT	LD50	5045	mg/kg
SCU	MUS	LDLO	6	gm/kg

METHANOL

IVN	RAT	LD50	2131	mg/kg
ORL	MUS	LD50	7300	mg/kg
ORL	RAT	LD50	5628	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated
STOT – single exposure	-	Hazardous: calculated

Symptoms/routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed/immediate effects: Immediate effects can be expected after short-term exposure.

Other information: Not applicable.

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

Ecotoxicity: No data available.

12.2 Persistence and degradability

Persistence/degradability: Biodegradable.

12.3 Bio accumulative potential

Bio accumulative potential: No bioaccumulation potential.

12.4 Mobility in soil

Mobility: Readily absorbed into soil.

12.5 Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6 Other adverse effects

Other adverse effects: Negligible ecotoxicity.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company. Dispose of contents and container according to national regulations.

Recovery operations: Not applicable.

Disposal of packaging: Not applicable.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

SECTION 14: TRANSPORT INFORMATION

14.1 UN number

UN number: UN1950

14.2 UN proper shipping name

14.3 Transport hazard class(es)

Transport class: 2.1

14.4 Packing group

14.5 Environmental Hazards

Environmentally hazardous: No

Marine pollutant: No

14.6 Special precautions for user

Special precautions: No special precautions.

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health & environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2 Chemical Safety Assessment

Chemical Safety: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

SECTION 16: OTHER INFORMATION

Other information

Other information This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

Phrases used in s.2 & s.3 H220: Extremely flammable gas.
H222: Extremely flammable aerosol.
H225: Highly flammable liquid and vapour.
H229: Pressurised container: May burst if heated.
H301: Toxic if swallowed.
H302: Harmful if swallowed.
H311: Toxic in contact with skin.
H314: Causes severe skin burns and eye damage.
H319: Causes serious eye irritation.
H331: Toxic if inhaled.
H336: May cause drowsiness or dizziness.
H370: Causes damage to organs.
H400: Very toxic to aquatic life.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product. Please note that due to the on-going change in regulation from CHIP to CLP, any MSDS information supplied by LMA is only considered accurate at the time of its creation. During this time classifications of substances may change. Therefore, it is possible that can art work and MSDS information may differ. As such if you have any concerns, we recommend you request a new MSDS from us every 6-12 months.